


FLUSH WALL CLOSURE

ECLISSE SYNTESIS® TECH - VERSIONS

SINGLE DOOR

Option with hinges on the vertical side
(Useful space between hinge and lock around **100 mm** less than the passage size)




A single frame for right-hinged or left-hinged opening

PASSAGE SIZE					OVERALL DIMENSIONS						
min	L	max	min	H	max	min	C	max	min	H1	max
300	÷	600	300	÷	1600	353	÷	653	353	÷	1653

DOUBLE DOOR

Option with hinges on the vertical side
(Useful space between hinge and lock around **150 mm** less than the passage size)



Not available with key-lock


PASSAGE SIZE					OVERALL DIMENSIONS						
min	L	max	min	H	max	min	C	max	min	H1	max
600	÷	1000	300	÷	1600	653	÷	1053	353	÷	1653
300+300	÷	500+500									

TOP-HUNG PANEL


BOTTOM-HINGED PANEL

REMOVABLE PANEL


Option with hinges on the horizontal side
(Useful space between hinge and lock around **100 mm** less than the passage size)



Hold open device supplied as standard



Safety chain device supplied as standard



Safety chain device supplied as standard

PASSAGE SIZE					OVERALL DIMENSIONS						
min	L	max	min	H	max	min	C	max	min	H1	max
300	÷	1600	300	÷	600	353	÷	1653	353	÷	653

NOTES

Single door:

- ▶ Supplied with push-pull opening system as standard.

Double door:

- ▶ Supplied with push-pull opening system as standard.

Dimensions are given in mm.

ECLISSE SYNTESIS® LINE BATTENTE
ECLISSE SYNTESIS® LINE BATTENTE WITH ELECTRIC STRIKE
ECLISSE SYNTESIS® LINE BATTENTE INCLINED
ECLISSE SYNTESIS® LINE BATTENTE GLASS
FLUSH WALL CLOSURE
ECLISSE MIMEST
ECLISSE 40 COLLECTION
BASEBOARD
ECLISSE DOORS
HANDLES
ACCESSORIES HARDWARE
ECLISSE WARRANTY